



Tarkett Australia Pty Ltd

Safetred Universal Plus

Safetred Universal plus is a tough durable safety flooring for use in any heavy duty application where safety underfoot is a priority. Safetred Universal Plus is suitable for use in more demanding areas such as busy commercial kitchens, food preparation areas and workshops which require a higher level of slip resistance. This product is available in 9 colours and has a R12 Slip resistance rating.

Products/Ranges: Safetred Universal Plus

Material Inputs, manufacturing, in-use **Product Stages Assessed:**

Product Type: Flooring product

CSI Masterformat: TBC

Licenced Site/s: Lenham, UK Licence Number: TAR:SA01:2022:PH Licence Date: 8th March 2022 Valid To: 8th March 2025 Standard: GGT International v4.0

Screening Date: 4th February 2022

PHD URL: http://www.globalgreentag.com/certifi-

cate/2366/



PHD Summary

Percentage Assessed:

100%

Inventory Threshold: 100ppm Product Level

Inventory Method: Nested Materials

GreenTag Banned List Compliant.

GreenTag PHD recognized by WELL™ & LEED ® Material Transparency & Optimization credits included below:

Meets Green Star * 'Buildings v1.0' ~ Credit 9: Responsible Finishes


Meets IWBI * WELL™ v1.0 as Recognized for ~ Feature 26 (Part 1); Feature 97 (Part 1); as a Compliant Technical Document (Audited) for ~ Feature 04 (Part 3); and, meets IWBI * WELL™ v2.0 as Recognized for ~ X07 (Parts 1, 3); X08 (Part 2); as a Compliant Technical Document (Audited) for ~ X06 (Part 2); X07 (Part 2); X08 (Part 1).

Meets USGBC LEED* v4.0 and v4.1 Rating Tool Credit as Recognized for MR Credit: Building Product Disclosure and Optimisation - Material Ingredients -Option 1: Material Ingredient Reporting, Option 2: International ACP - REACH Optimisation.

Independent third party assessment for worker, user, and environmental exposure to any Carcinogens, Mutagens, Reproductive Toxicant or Endocrine Disruptors.

> INGREDIENT HAZARD DISCLOSURE, RISK ASSESSMENT, & IN USE HEALTH, % by mass.

> > 100%



Declared by: Global GreenTag International Pty Ltd



David Baggs CEO & Program Director Verified compliant with: ISO 14024 & ISO 17065

1.0 Scope

The Global GreenTag International (GGT) Product Health Declaration (PHD) has been designed to provide an additional level of service to the green product sector in facilitating an easier understanding of both the hazard and risks associated with any certified products, and is intended to indicate:

- Chemical hazards of both finished product and unique ingredients to a minimum level of 100ppm for final product throughout the product life cycle (including any VOC or other gaseous emissions);
- An assessment of exposure or risk associated with ingredient handling, product use, and disposal in relation to established mitigation and management processes:

It is not intended to assess:

- i. substances used or created during the manufacturing process unless they remain in the final product; or
- ii. substances created after the product is delivered for end use (e.g., if the product unusually degrades, combusts or otherwise changes chemical composition).

GGT PHDs are only issued to products that have passed GGT Standards' certification requirements. The Level of Assessment (BronzeHEALTH, SilverHEALTH, GoldHEALTH or PlatinumHEALTH) of a PHD rating relates ONLY to a Human Health Toxicity Assessment and is declared separately and not equivalent to the overall Bronze, Silver Gold or Platinum Green Tag Certification Mark Tier Levels of LCARate.

1.2 Preparing a PHD

GGT PHDs are prepared in the format of a transparency document which utilizes Hazard Classifications from the UN Globally Harmonised System of Classification and Labelling of Chemicals (GHS). Hazard Classifications are then risk assessed with a focus on the In Use stage for an outcome of Certification. Assessments are undertaken by GGT Qualified Exemplar Global Lead Auditors and subsequently accepted for Certification by the GGT Program Director (also a Qualified Exemplar Global Lead Auditor) under the International Standard v4.0/4.1, Personal Products Standard v1.0/1.1, or Cleaning Products Standard v1.1/1.2 and above Program Rules.

1.3 External Peer Review

Every GGT PHD is independently peer-reviewed by an external Consultant Toxicologist and Member of the Australasian College of Toxicology & Risk Assessment.

2.0 Declaration of Ingredients

Where a manufacturer wishes recognition under a rating program that requires transparency of ingredients, such as LEED * v4.0 & v4.1, WELL * v1.0 & v2.0, Green Star *, the following information is declared from the audit:

Colour	Ingredient Hazard Disclosure
Green	Level 4 The hazard level of this ingredient indicates that the ingredient has no toxic hazard statements with no identified health effects.
Yellow	Level 3 The hazard level of this ingredient indicates that the ingredient is mildly toxic and/or has short/medium term reversible health effects.
Orange	Level 2 The hazard level of this ingredient indicates that the ingredient is moderately toxic and/or with a moderate health effects.
Red	Level 1 The hazard level of this ingredient indicates that the ingredient is highly toxic with a potential for severe health effects.
Black	Level 0 The hazard level of this ingredient indicates that the ingredient is highly toxic with a potential for severe health effects and is banned from being detectable above trace amounts in the final product.
Grey	Grey Chemical Not able to be categorised due to lack of toxicity impact information.
Colour	Risk Assessment & In Use Health Assessment Outcome
Green	No Concerns The risk assessment outcomes for the hazard level and percentage of ingredient used in the product after risk assessment is considered highly unlikely and therefore without concerns.
Yellow	Human Health Comment The risk assessment outcome for the hazard level and percentage of ingredient used in the product is after risk assessment considered low with an unlikely potential risk.
Orange	Issue of Concern or Issue of Concern Minimised The risk assessment outcome for the hazard level and percentage of ingredient used in the product is after risk assessment considered low to high with a higher than unlikely potential for risk.
Red	Red Light Comment or Red Light Comment Minimised The risk assessment outcome for the hazard level and percentage of ingredient used in the product is after risk assessment considered low to extremely high with a moderate potential for risk.
Dark Red	Red Light Exclusion The risk assessment outcome for the hazard level and percentage of ingredient used in the product is after risk assessment considered medium to extremely high with a likely potential for risk.
Grey	Grey Chemical Not able to be categorised due to lack of toxicity impact information.
Black	Banned Ingredients Level 0 Hazard Level categorised chemicals such as Substances of Very High Concern in the International Standard v4.0/v4.1 and/or Petroleum, Parabens plus a wide range of additional compounds stipulated by the Personal Products Standard v1.0/1.1 and Cleaning Products Standard v1.1/1.2

Global GreenTag International Pty Ltd (Global GreenTag) is not a medical professional organisation. Global GreenTag does not purport to provide medical advice, and makes no warranty, representation, or guarantee regarding the declaration that it provides in relation to any allergies, chemical sensitivities or any other medical condition, nor does Global GreenTag assume any liability whatsoever arising out of the application or use of any product or piece of equipment that has been chemically assessed by Global GreenTag.

The chemical assessments carried out provide transparent information peer reviewed by a consultant toxicologist regarding the chemical make-up and ingredients of certain materials and products, but such assessments are not to be taken as any form of medical assessment or health advice and are not targeted towards providing specific solutions to allergenic conditions or any other type of medical concerns.

Users must carry out their own investigations if they are concerned about specific medical conditions and the impact of certain products or ingredients in relation to specific medical concerns.

Global GreenTag takes no responsibility and is not liable in any way with respect to any medical or health issues arising from a person's use of materials or products that have been chemically assessed by Global GreenTag. Global GreenTag shall not be liable for any direct, indirect, punitive, incidental, special or consequential damages to property or life whatsoever, arising out of or connected with the use or misuse of any materials or products that have been assessed by Global GreenTag.



Ingredient Name	CAS Number OR Function	Proportion in finished product	GHS, IARC & Endocrine Category	REACH Compliance	Ingredient Assessment	Whole Of Life Assessment	In Use Health Assessment	Comment
Polyvinyl Chloride (PVC)	9002-86-2	10-20%	H315(Skin Irrit. 2) H319((Eye Irrit. 2) H335(STOT SE 3) H400(Aquatic Acute 1) H412(Aquatic Chronic 3)	OK			_	PVC- Paste is toxic to aquatic life with long lasting effects. It casues skin and eye irritation in humans. However, the manufacturer of the product operates under Environmental Management System and an Occupational Health and Safety System, therefore the risk is considered low. The substance is chemically combined into the final product, the hazards will not present in the final product. Therefore, it is not expected to cause harm to the users.
PVC Scraps	Base ma- terial	35-45%	None	ОК			_	Recycled Content: Post-I Nanomaterials: No
i-isononyl-cyclohex- ane-1,2-dicarboxylate	166412- 78-8	3-10%	None	ОК				Recycled Content: None Nanomaterials: No
1,4-Benzenedicarbox- ylicacid, 1,4-dibutyl ester	Plasticizer	1-5%	None	ОК				Recycled Content: None Nanomaterials: No
Ca-Zn soap	Stabiliser	<1%	None	ОК				Recycled Content: None Nanomaterials: No
Epoxidised soybean oil	8013-07-08	<1%	H317(Skin Sens 1)	ОК			_	Epoxidised soybean oil can cause skin irritation if contacted However, the manufacturer has an Occupational Health and Safety System in place, so the risks is considered low in the manufacturing stage. The substance is chemically combined into the final product, the hazards will not present in the final product. Therefore, it is not expected to cause harm to the users.
Triisotridecyl phosphite	77745-66-5	<1%	H317(Skin Sens 1)	OK	_	_	_	Triisotridecyl phosphite can cause skin irritation if contacted However, the manufacturer has an Occupational Health and Safety System in place, so the risks is considered low in the manufacturing stage. The substance is chemically combined into the final product, the hazards will not present in the final product. Therefore, it is not expected to cause harm to the users.
Calcium carbonate (synthetic)	471-34-1	20-30%	None	ОК				Recycled Content: None Nanomaterials: No
Magnesium carbonate	546-93-0	10-20%	None	ОК				Recycled Content: None Nanomaterials: No
Titanium dioxide	13463-67-7	<1%	H351(Carc 2)	ОК	_		_	The Titanium dioxide may cause cancer if contacted. However, the manufacturer of the product operates under an Occupational Health and Safety System and therefore risks are considered low at the manufacturing stage. The substance is chemically embedded into the final product, the hazards will not present in the final product. Therefore, it is not expected to cause harm to the users.
CI Pigment Black 7	1333-86-4	<1%	None	ОК				Recycled Content: None Nanomaterials: No
CI Red 144	5280-78-4	<1%	None	ОК				Recycled Content: None Nanomaterials: No
CI Red 101	90452-21-4	<1%	None	ОК				Recycled Content: None Nanomaterials: No
CI Black 11	12227-89-3	<1%	H332(Acute Tox. 4)	OK				Recycled Content: None Nanomaterials: No
CI Blue 15:1	12239-87-1	<1%	None	OK				Recycled Content: None Nanomaterials: No



5590-18-1							
3390-16-1	<1%	None	OK				Recycled Content: None Nanomaterials: No
5580-57-4	<1%	None	ОК				Recycled Content: None Nanomaterials: No
N/A	60-70%	None	OK				Recycled Content: None Nanomaterials: No
603-784-8	20-25%	None	ОК				Recycled Content: None Nanomaterials: No
166412- 78-8	0-5%	None	OK				Recycled Content: None Nanomaterials: No
Photopoly- merizable varnish	<1%	H315(Skin Irrit. 2) H318(Skin Sens.) H317(Eye Dam. 1) H412(Aquatic Chronic 3)	ОК	_	_		This mixture can cause skin and eye irritation if contacted. However, the manufacturer has an Occupational Health and Safety System in place, so the risks is considered low in the manufacturing stage. The substance is chemically combined into the fina product, the hazards will not presen in the final product. Therefore, it is not expected to cause harm to the users.
57472-68-1	<1%	H315(Skin Irrit. 2) H318(Eye Dam. 1) H317(Eye Dam. 1)	ОК				Dipropylene glycol diacrylate can cause skin and eye irritation if contacted. However, the manufacturer has an Occupational Health and Safety System in place, so the risks is considered low in the manufacturing stage. The substance is chemically combined into the final product, the hazards will not present in the final product. Therefore, it is not expected to cause harm to the users.
Binder	0.5%	H315(Skin Irrit. 2) H319(Eye Irrit. 2)	ОК				Aliphatic urethane Acrylate can cause skin and eye irritation if contacted. However, the manufacturer has an Occupational Health and Safety System in place, so the risks is considered low in the manufacturing stage. The substance is chemically combined into the final product, the hazards will not present in the final product. Therefore, it is not expected to cause harm to the users.
42594-17-2	<1%	H317(Eye Dam. 1) H411(Aquatic Chronic 2)	ОК				Tricyclodecane dimethanol diacry- late can cause skin and eye irritation if contacted. However, the manufac- turer has an Occupational Health an Safety System in place, so the risks is considered low in the manufacturin stage. The substance is chemically combined into the final product, the hazards will not present in the final product. Therefore, it is not expected to cause harm to the users.
1344-28-1	1-5%	None	ОК				Recycled Content: None Nanomaterials: No
409-21-2	1-5%	None	ОК				Recycled Content: None Nanomaterials: No
144031- 03-8	<1%	H318(Eye Dam. 1)	ОК				Poly(oxy-1,2-ethanediyl), aisodecyl-w-hydroxy-, reaction products with maleic anhydride)can cause eye damage if contacted. However, the manufacturer has an Occupational Health and Safety System in place, so the risks is considered low in the manufacturing stage. The substance is chemically combined into the fina product, the hazards will not presen in the final product. Therefore, it is not expected to cause harm to the users.
	N/A 603-784-8 166412- 78-8 Photopolymerizable varnish 57472-68-1 42594-17-2 1344-28-1 409-21-2	N/A 60-70% 603-784-8 20-25% 166412- 78-8 0-5% Photopolymerizable varnish 57472-68-1 <1% Binder 0.5% 42594-17-2 <1% 1344-28-1 1-5% 409-21-2 1-5%	N/A 60-70% None 603-784-8 20-25% None 166412- 78-8 0-5% None H315(Skin Irrit. 2) H318(Skin Sens.) H317(Eye Dam. 1) H412(Aquatic Chronic 3) F7472-68-1 <1% H318(Eye Dam. 1) H317(Eye Dam. 1) H317(Eye Dam. 1) H319(Eye Irrit. 2) H319(Eye Irrit. 2) 42594-17-2 <1% H317(Eye Dam. 1) H318(Eye Dam. 1)	N/A 60-70% None OK 603-784-8 20-25% None OK 166412- 78-8 0-5% None OK Photopolymerizable varnish	N/A 60-70% None OK 603-784-8 20-25% None OK 166412- 78-8 0-5% None OK Photopolymerizable varnish <1% H315(Skin Irrit. 2) H318(Skin Sens.) H317(Eye Dam. 1) H317(Eye Dam. 1) H317(Eye Dam. 1) H317(Eye Dam. 1) H319(Eye Irrit. 2) OK H315(Skin Irrit. 2) H318(Eye Dam. 1) H317(Eye Dam. 1) OK H317(Eye Dam. 1) OK 42594-17-2 <1% H319(Eye Irrit. 2) OK 42594-17-2 <1% H317(Eye Dam. 1) H317(Eye Dam. 1) OK 1344-28-1 1-5% None OK 144031-	N/A 60-70% None OK 603-784-8 20-25% None OK 166412- 78-8 O-5% None OK Photopolymerizable varnish Chronic 3) 57472-68-1 <1% H315(Skin Irrit. 2) H318(Skin Irrit. 2) H319(Eye Dam. 1) H412(Aquatic Chronic 3) Binder O.5% H315(Skin Irrit. 2) H319(Eye Dam. 1) H319(Eye Irrit. 2) White the state of the sta	N/A 60-70% None OK



Additive	Eliminate moisture	<1%	H318(Eye Dam. 1) H315(Skin Irrit. 2) H335(STOT SE 3)	ОК		This additive can cause skin and eye irritation if contacted. However, the manufacturer has an Occupational Health and Safety System in place, so the risks is considered low in the manufacturing stage. The substance is chemically combined into the final product, the hazards will not present in the final product. Therefore, it is not expected to cause harm to the users.
Calcium oxide	1305-78-9	<1%	H318(Eye Dam. 1) H315(Skin Irrit. 2) H335(STOT SE 3)	ОК		Calcium oxide can cause skin and eye irritation if contacted. However, the manufacturer has an Occupational Health and Safety System in place, so the risks is considered low in the manufacturing stage. The substance is chemically combined into the final product, the hazards will not present in the final product. Therefore, it is not expected to cause harm to the users.

COMMENTS:

VOC Emissions	: Sum of VOC (TVOC	i) was below or equal to the	e limit values of 100ug	/m3 after 28 days.	The product qualified	for the Tarkett Indoor	r Air Quality Gold I	abel.(Eurofins Co	ertifica-
tion Body VOC)									